



Calora European-Style Convectors



OCEH
White



OCEM
Stainless Steel



OCEB
White



This efficient and perfectly silent natural convection heating system provides uniform room temperatures for increased comfort. The convector is available in three different heights compatible with all room types. It can be equipped with a built-in (TH models) or wall-mounted (OTH models) electronic thermostat that meets the highest performance standards. When combined with the wall-mounted thermostat, the convector may be installed on an exterior wall. Calora and its thermostats provide an ingenious heating system that maximizes both comfort and energy efficiency.

Features

Color

- Standard:

BL White

AM Almond

- Optional (10\$ upcharge and 5 days production lead time):

NL Semi-Gloss Black

CM Metallic Charcoal

BZ Bronze

AE Metallic Silver

AL Aluminum

SA Sand

Note: Due to the printing, the colors may vary from the actual colors.

Finish

- Standard: epoxy/polyester powder paint.
- Optional: stainless steel (only grilles are painted black).

Voltage

- 240/208V, 50/60 Hz, 1-phase.

Construction

- 20-gauge steel or 22-gauge stainless steel.
- Warm air outlet that directs the air to the centre of the room.
- Bar grilles prevent insertion of foreign objects; smooth-finish paint is washable and anti-yellowing.
- High-limit temperature control with automatic reset.

Heating element

- Quiet aluminum monoblock element.

Watt density

- OCEH: 850W/ft. (2800W/m)
- OCEM: 700W/ft. (2320W/m)
- OCEB: 500W/ft. (1700W/m)

Control

- Built-in electronic thermostat (TH models)
- Wall-mounted electronic thermostat (OTH models).

Installation

- 2 in. (51 mm) minimum clearance to floor.
- The convector's wall mounting bracket is connected to the power supply.
- Simply place the convector on the bracket to make it operational.

Warranty

- 5-year warranty against defects.
- (The warranty is valid only if the heater is controlled by a proportional pulsing electronic thermostat with a cycle of 15 seconds maximum and the junction box must be fixed to the wall with the supplied anchor.)*

Application

- Kitchen, living room, family room, bedroom, bay window, basement.

Models

Watts	Volts	Product #		Price		Length	
		Non Programmable Built-In Thermostat	Non Programmable Wall-Mounted Thermostat	Standard Models	Stainless Steel	in.	m
Height 27" (685 mm) 850W/ft. (2800W/m)							
500/375	240/208	OCEH0500-TH	OCEH0500-OTH	538.00	659.00	10 5/8	270
1000/750	240/208	OCEH1000-TH	OCEH1000-OTH	597.00	733.00	16 1/2	418
1500/1125	240/208	OCEH1500-TH	OCEH1500-OTH	653.00	803.00	23	584
2000/1500	240/208	OCEH2000-TH	OCEH2000-OTH	725.00	893.00	28 1/8	714
2500/1875	240/208	OCEH2500-TH	OCEH2500-OTH	786.00	969.00	34	862
3000/2250	240/208	OCEH3000-TH	OCEH3000-OTH	845.00	1043.00	41 1/8	1044
Height 18 1/2" (470 mm) 700W/ft. (2320W/m)							
500/375	240/208	OCEM0500-TH	OCEM0500-OTH	522.00	639.00	13 1/2	344
1000/750	240/208	OCEM1000-TH	OCEM1000-OTH	574.00	704.00	19 7/16	492
1500/1125	240/208	OCEM1500-TH	OCEM1500-OTH	644.00	792.00	26 1/2	674
2000/1500	240/208	OCEM2000-TH	OCEM2000-OTH	710.00	874.00	34	862
2500/1875	240/208	OCEM2500-TH	OCEM2500-OTH	771.00	950.00	41 1/8	1044
3000/2250	240/208	OCEM3000-TH	OCEM3000-OTH	832.00	1027.00	48 3/8	1229
Height 14" (356 mm) 500W/ft. (1700W/m)							
500/375	240/208	OCEB0500-TH	OCEB0500-OTH	550.00	674.00	19 7/16	492
1000/750	240/208	OCEB1000-TH	OCEB1000-OTH	608.00	747.00	26 1/2	674
1500/1125	240/208	OCEB1500-TH	OCEB1500-OTH	680.00	837.00	36 3/8	924
2000/1500	240/208	OCEB2000-TH	OCEB2000-OTH	741.00	913.00	46 7/16	1179
2500/1875	240/208	OCEB2500-TH	OCEB2500-OTH	802.00	989.00	62 3/16	1579
3000/2250	240/208	OCEB3000-TH	OCEB3000-OTH	864.00	1067.00	69 5/16	1760

Add «BL» for white, «AM» for almond and «SS» for stainless steel. For stainless steel models, only the grille are black painted.

Warranty is valid only if the heater is controlled by a proportional electronic pulsing line thermostat with a cycle of 15 seconds maximum and the junction box must be fixed to the wall with the supplied anchor.

